



12th April 2021

MEDIA RELEASE

Electronics and connected solutions

The new compact 8" CCI 800 ISOBUS terminal offers the optimum size to control all functions on a large number of machines.

Presented at the last international trade shows, the new CCI 800 terminal is available from September 2020 for the entire KUHN range.

It is characterized by its 8-inch/ 20.3 cm screen specially developed to avoid the mirror effect of seeing one's own reflection on the terminal and thus retains an excellent view in the presence of sunlight.

Like the CCI 1200 terminal, all useful information is displayed on the same screen to avoid paging between different applications. The main display comes with mini views on the side of the screen, allowing you to display other information. Just select the desired mini view for its display to switch to the main screen.

The main functionalities:

The functionalities are identical to those of the CCI 1200 terminal:

- Section Control :
 - automatic management of rows, working width, nozzles, ... via DGPS or RTK,
 - automatic management of up to 4 different products (booms),
- Application rate modulation:
 - Compatible with all SHP and ISO-XML modulation map providers:
 - Automatic management of up to 4 modulation maps,
 - Left/right modulation with a centrifugal fertiliser spreader,
 - Up to 32 application rates for a same product or boom,
 - Compatible with ISOBUS or non-ISOBUS sensors biomass/N-Sensor,
- Guidance assistance with new modes: pivot / A + angle,

- Remote View: remote viewing of the terminal's screen,
- Online CCI update: remote software update,
- Agrirouter Ready: the terminal can receive and transfer data via the agrirouter data exchange platform,
- Connection of a camera, automatic display when reversing. It is also possible to connect a second camera with a miniplexer,
- ISOBUS certification by the AEF.

<<<ENDS>>>

Media contact:

Emily Perry
Norwood Marketing Manager
06 356 4920
Emily.Perry@norwood.co.nz
www.kuhn.co.nz



